

DERWENT-ACC-NO: 2003-088410

DERWENT-WEEK: 200308

COPYRIGHT 2005 DERWENT INFORMATION LTD

TITLE: Bus keeper circuit

INVENTOR: PARK, H J

PATENT-ASSIGNEE: PARK H J[PARKI]

PRIORITY-DATA: 2001KR-0002977 (January 18, 2001)

PATENT-FAMILY:

PUB-NO	PUB-DATE	LANGUAGE
PAGES MAIN-IPC		
KR 2002061893 A	July 25, 2002	N/A
001 G06F 011/22		

APPLICATION-DATA:

PUB-NO	APPL-DESCRIPTOR	APPL-NO
APPL-DATE		
KR2002061893A	N/A	2001KR-0002977
January 18, 2001		

INT-CL (IPC): G06F011/22

ABSTRACTED-PUB-NO: KR2002061893A

BASIC-ABSTRACT:

NOVELTY - A bus keeper circuit is provided to easily embody a circuit designed as a three-state bus structure to an FPGA(Field Programmable Gate Array) and to make the circuit carry out a stable operation by applying to the FPGA.

DETAILED DESCRIPTION - A NAND gate(46) generates a high level signal if one of the enable signals(EN1-EN6) is the low level. A three-state driver(44) makes the output signal of a flip-flop(42) feedback to the three-state bus and an input terminal(D) of the flip-flop(40) by responding to the output signal of the NAND gate of the low level. The flip-flop(42) stores the data

output from
the three-state driver by responding to a clock signal(CLK). In this
case, the
bus keeper circuit keeps the previous data stored in the flip-
flop(42) because
the data, transferred to the three-state bus from the function
blocks, do not
exist. The bus keeper circuit makes the flip-flop stores the data
transferred
to the three-state bus by responding to the clock signal and in case
of not
existing the data transferred to the three-state bus, transfers the
data
previously stored data output from the flip-flop by making the three-
state
driver enabled.

CHOSEN-DRAWING: Dwg.1/10

TITLE-TERMS: BUS KEEPER CIRCUIT

DERWENT-CLASS: T01

EPI-CODES: T01-G02A;

